





Green Pin® Lifting Eye S/S-GR5

Grade 5 stainless steel lifting eye

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] CE



ALI



working load limit	diameter thread	diameter base	diameter eye outside	diameter eye inside	length	thickness base	diameter	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
0.12	M6 x 1.00	20	34	20	20	17	7	0.05
0.2	M8 x 1.25	20	34	20	24	17	7	0.05
0.4	M10 x 1.50	20	38	22	30	19	8	0.08
0.6	M12 x 1.75	25	47	27	36	23	10	0.14
0.8	M14 x 2.00	30	57	30	40	27	14	0.26
1	M16 x 2.00	36	63	35	53	31	14	0.37
1.5	M18 x 2.50	36	63	35	53	31	14	0.49
2	M20 x 2.50	40	72	40	58	34	16	0.55
2.5	M22 x 2.50	42	82	45	64	38	19	0.78
3	M24 x 3.00	55	95	55	84	40	20	1.12





Green Pin® Lifting Eye DIN580 length S/S-GR5

Grade 5 stainless steel lifting eye length as DIN580

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] CE



ALDINI



working load limit	diameter thread	diameter base	diameter eye outside	diameter eye inside	length	thickness base	diameter	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
0.2	M8 x 1.25	20	34	20	13	17	7	0.05
0.4	M10 x 1.50	20	38	22	17	19	8	0.08
0.6	M12 x 1.75	25	47	27	21	23	10	0.14
0.8	M14 x 2.00	30	57	30	27	27	14	0.26
1	M16 x 2.00	36	63	35	27	31	14	0.37
1.5	M18 x 2.50	36	63	35	30	31	14	0.49
2	M20 x 2.50	40	72	40	30	34	16	0.55
2.5	M22 x 2.50	42	82	45	36	38	19	0.78
3	M24 x 3.00	55	95	55	36	40	20	1.12