




CSEI



## Green Pin® Sling Hook S S/S-GR5



### Grade 5 stainless steel swivel sling hook

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>b</sup>
- **Note:** equipped with a stainless steel washer

| for chain diameter |                                                            | working load limit | length | length inside | width inside | width opening | thickness | width | width outside | length outside | diameter | thickness | weight each |
|--------------------|------------------------------------------------------------|--------------------|--------|---------------|--------------|---------------|-----------|-------|---------------|----------------|----------|-----------|-------------|
| mm                 | inch                                                       | t                  | a mm   | b mm          | c mm         | d mm          | e mm      | f mm  | g mm          | h mm           | i mm     | j mm      | kg          |
| 6                  | <sup>7</sup> / <sub>32</sub>                               | 0.7                | 100    | 33            | 32           | 26            | 15        | 20    | 72            | 164            | 12       | 6         | 0.55        |
| 7 - 8              | <sup>1</sup> / <sub>4</sub> - <sup>5</sup> / <sub>16</sub> | 1.2                | 126    | 40            | 37           | 30            | 20        | 24    | 87            | 200            | 14       | 8         | 1           |
| 10                 | <sup>3</sup> / <sub>8</sub>                                | 1.6                | 159    | 47            | 47           | 33            | 24        | 29    | 106           | 250            | 16       | 11        | 1.9         |
| 13                 | <sup>1</sup> / <sub>2</sub>                                | 2.7                | 189    | 59            | 58           | 37            | 32        | 39    | 133           | 307            | 21       | 14        | 3.42        |



CROI



## Green Pin® Grab Hook E S/S-GR5

### Grade 5 stainless steel eye grab hook

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>b</sup>

| for chain diameter |                                                            | working load limit | length | inside length eye | inside width eye | opening | thickness | width | width outside | length | width | thickness | weight each |
|--------------------|------------------------------------------------------------|--------------------|--------|-------------------|------------------|---------|-----------|-------|---------------|--------|-------|-----------|-------------|
| mm                 | inch                                                       | t                  | a mm   | b mm              | c mm             | d mm    | e mm      | f mm  | g mm          | h mm   | i mm  | j mm      | kg          |
| 6                  | <sup>7</sup> / <sub>32</sub>                               | 0.7                | 41     | 24                | 23               | 8       | 24        | 20    | 42            | 94     | 9     | 6         | 0.25        |
| 7 - 8              | <sup>1</sup> / <sub>4</sub> - <sup>5</sup> / <sub>16</sub> | 1.2                | 53     | 27                | 26               | 10      | 33        | 23    | 53            | 115    | 10    | 8         | 0.32        |
| 10                 | <sup>3</sup> / <sub>8</sub>                                | 1.6                | 65     | 38                | 36               | 12      | 40        | 29    | 66            | 146    | 14    | 10        | 0.53        |
| 13                 | <sup>1</sup> / <sub>2</sub>                                | 2.7                | 83     | 42                | 41               | 15      | 56        | 40    | 88            | 183    | 16    | 12        | 1.96        |