





ELI



Green Pin® Eye Nut S/S-GR5


Grade 5 stainless steel eye nut

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI ^b CE

working load limit	diameter thread	diameter base	width	width inside	thickness base	length inside	diameter	thickness	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
0.12	M6 x 1.00	31	51	30	14	44	11	6	0.15
0.2	M8 x 1.25	31	51	30	14	44	11	6	0.15
0.4	M10 x 1.50	31	51	30	14	44	11	6	0.15
0.6	M12 x 1.75	39	56	32	15	48	12	6	0.23
0.8	M14 x 2.00	39	56	32	15	48	12	6	0.23
1	M16 x 2.00	44	65	37	17	60	14	8	0.37
1.5	M18 x 2.50	44	65	37	17	60	14	8	0.37
2	M20 x 2.50	44	65	37	17	60	14	8	0.37
2.5	M22 x 2.50	52	79	48	21	75	16	11	0.63
3	M24 x 3.00	52	79	48	21	75	16	11	0.63
3.5	M27 x 3.00	52	79	48	21	75	16	11	0.63



PASI



Green Pin® Weld-On Transport Ring S/S-GR5

Grade 5 stainless steel weld-on transport ring

- **Material:** AISI 316, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 CE
- **Note:** regarding the selection of welding material, respecting parent and PASI materials, please refer to EN 3581 for manual metal arc welding and to EN ISO 14343 for arc welding

working load limit	diameter	width inside	length inside	length base	height base	length	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	kg
0.75	13	40	42	35	28	83	0.4
1.25	18	45	48	42	33	99	0.8
3.2	22	55	57	49	42	121	1.4
5	26	70	67	64	50	143	2.5

INFO